



SEM600
Motor Controller
 US Pat. No. 7,956,558

Product Highlights

- **No Motor speed sensor**
- **No steering angle sensor**
- **Permanent differential control**
- **Automatic differential lock**

The SEM Dual motor power panel control drives 2 separately excited traction motors providing continuous differential operation and automatic differential lock when needed.

(US PAT. No. 7,956,558)

No motor speed sensor and steering angle sensor are needed.

When used in conjunction with a GP400 module in the base control box, a P600 pump controller and a GP440 module in the platform control box the SEM Dual motor controller provides a complete control solution for electric boom vehicle with electric drive.

Electric Scissor lift control can be achieved with the addition of a GP400 module in the ground control box and a P600 pump motor controller.



General Features

- 480A traction motor continuous current
- CAN bus interface
- RS232 connection to hand-held "EZcal" for calibration and diagnostics
- "FLASH" memory allows configuration to specific customer needs
- Failsafe functionality to comply with EN 954-3

Technical Data

Power supply	48V		
Motor Peak Rating	15HP		For Each Motor
Waterproof	IP 65		
Working Temperature	-40 + 60°C		
Overall Dimensions	8 ½" x 9 ¾" x 2 ½"		L x W x H
	216 x 248 x 64 mm		